


VT8

The compact footprint and ease of use are two main features that make the VT8 light tower one of the top models in the USR® Tower Light range. High performance balanced with low cost allowed the VT8 to become the best-seller model in the extra-European market.



		VT8 K	VT8 M	VT8 Y
TECHNICAL DATA				
Lifting system	-	Manual	Manual	Manual
Min. dim.	mm	2650 x 1300 x 2460	2650 x 1300 x 2460	2650 x 1300 x 2460
Max. dim.	mm	2650 x 2460 x 8000	2650 x 2460 x 8000	2650 x 2460 x 8000
Dry Weight	kg	719	719	719
Lamps power	W	4 x 1000	4 x 1000	4 x 1000
Lamps type	-	Metal Halide	Metal Halide	Metal Halide
Total lumen	Lm	360.000	360.000	360.000
Certified illuminated area	m²	4200	4200	4200
Mast rotation	°	340	340	340
Certified wind speed resistance	km/h	80	80	80
Tank capacity	liters	75	75	75
Liquid containment tank (110%)	-	No	No	No
Engine model	-	Kubota D1105	Mitsubishi L3E	Yanmar 3TN
Cylinders	-	3	3	3
Engine speed	rpm	1500 / 1800	1500 / 1800	1500 / 1800
Engine cooling	-	Water	Water	Water
Alternator	-	8.0 kVA - 230 V - 50/60 Hz	8.0 kVA - 230 V - 50/60 Hz	8.0 kVA - 230 V - 50/60 Hz
Outlet socket	-	3.0 kVA - 230 V - 50/60 Hz	3.0 kVA - 230 V - 50/60 Hz	3.0 kVA - 230 V - 50/60 Hz
Running time	h	40	40	40
Avg. sound pressure level	dB(A) at 7m	68	68	68
Standard trailer	-	Low speed site-tow trailer	Low speed site-tow trailer	Low speed site-tow trailer

THE BEST SELLER

The VT8 is the best seller model of light tower in the extra-european market, thanks to the vertical mast and the high quality features granted by USR® Tower Light.

TOP STABILITY

Five fully integrated stabilizers will ensure maximum stability in every application.

VERTICAL MAST

A telescopic vertical mast with manual lifting system and a maximum height of 8 meters.

METAL HALIDE LAMPS

4x1000W powerful metal halide lamps able to illuminate medium and big working areas.

TRAILER OPTIONS

The VT8 is equipped as standard with a low speed trailer but it can be also mounted on a straight road trailer.

ENGINE OPTIONS

You can choose the engine you prefer between Yanmar 3TN, Mitsubishi L3 and Kubota D1105.



OPTIONS AVAILABLE

Road trailer type A (straight)

Road axle only

110V outlet socket

Pre-heating system

Earth picket with 5m cable

Main/generator selector switch

Plastic box for documents

Dedicated single colour (min. 5 units)

Dedicated double colour (min. 5 units)

Chalwyn valve

Certified spark arrestor

Hot-dip zinc coating of mast sections (min. 5 units)

Ball hitch type 50 mm

Eyelet hitch type 50 mm

French hitch type 68mm for road trailer type C

Eco panel with digital timer and darkness sensor